

# Manual on Uniform Traffic Control Devices

for Streets and Highways

**2009 Edition**

Including Revision 1 dated May 2012

Revision 2 dated May 2012

and Revision 3 dated July 2022



U.S. Department of Transportation  
Federal Highway Administration



# Manual on Uniform Traffic Control Devices

## 2009 Edition

Including Revision 1 dated May 2012  
Revision 2 dated May 2012  
and Revision 3 dated July 2022

## PART 3. MARKINGS

### **CHAPTER 3A. GENERAL**

|               |   |     |
|---------------|---|-----|
| Section 3A.01 | Functions and Limitations.....  | 347 |
| Section 3A.02 | Standardization of Application .....                                    | 347 |
| Section 3A.03 | Maintaining Minimum Pavement Marking Retroreflectivity .....            | 347 |
| Section 3A.04 | Materials .....   | 348 |
| Section 3A.05 | Colors .....  | 348 |
| Section 3A.06 | Functions, Widths, and Patterns of Longitudinal Pavement Markings ..... | 349 |

### **CHAPTER 3B. PAVEMENT AND CURB MARKINGS**

|               |   |     |
|---------------|---|-----|
| Section 3B.01 | Yellow Center Line Pavement Markings and Warrants .....   | 350 |
| Section 3B.02 | No-Passing Zone Pavement Markings and Warrants .....  | 353 |
| Section 3B.03 | Other Yellow Longitudinal Pavement Markings .....   | 355 |
| Section 3B.04 | White Lane Line Pavement Markings and Warrants .....  | 357 |
| Section 3B.05 | Other White Longitudinal Pavement Markings .....  | 372 |
| Section 3B.06 | Edge Line Pavement Markings .....   | 372 |
| Section 3B.07 | Warrants for Use of Edge Lines .....  | 372 |
| Section 3B.08 | Extensions Through Intersections or Interchanges .....  | 372 |
| Section 3B.09 | Lane-Reduction Transition Markings .....  | 375 |
| Section 3B.10 | Approach Markings for Obstructions.....   | 377 |
| Section 3B.11 | Raised Pavement Markers – General .....   | 377 |
| Section 3B.12 | Raised Pavement Markers as Vehicle Positioning Guides with Other Longitudinal<br>Markings ..... | 380 |
| Section 3B.13 | Raised Pavement Markers Supplementing Other Markings.....                                       | 380 |
| Section 3B.14 | Raised Pavement Markers Substituting for Pavement Markings.....                                 | 381 |
| Section 3B.15 | Transverse Markings.....  | 382 |
| Section 3B.16 | Stop and Yield Lines .....  | 382 |
| Section 3B.17 | Do Not Block Intersection Markings .....  | 383 |
| Section 3B.18 | Crosswalk Markings .....  | 384 |
| Section 3B.19 | Parking Space Markings .....  | 386 |
| Section 3B.20 | Pavement Word, Symbol, and Arrow Markings.....  | 388 |
| Section 3B.21 | Speed Measurement Markings .....  | 394 |
| Section 3B.22 | Speed Reduction Markings .....  | 394 |
| Section 3B.23 | Curb Markings .....   | 395 |
| Section 3B.24 | Chevron and Diagonal Crosshatch Markings.....   | 396 |
| Section 3B.25 | Speed Hump Markings .....   | 396 |
| Section 3B.26 | Advance Speed Hump Markings .....   | 396 |

Rev. 3

### **CHAPTER 3C. ROUNDABOUT MARKINGS**

|               |   |     |
|---------------|---|-----|
| Section 3C.01 | General .....   | 400 |
| Section 3C.02 | White Lane Line Pavement Markings for Roundabouts .....               | 414 |
| Section 3C.03 | Edge Line Pavement Markings for Roundabout Circulatory Roadways ..... | 414 |
| Section 3C.04 | Yield Lines for Roundabouts.....                                      | 414 |
| Section 3C.05 | Crosswalk Markings at Roundabouts.....                                | 414 |
| Section 3C.06 | Word, Symbol, and Arrow Pavement Markings for Roundabouts .....       | 414 |
| Section 3C.07 | Markings for Other Circular Intersections .....                       | 415 |

### **CHAPTER 3D. MARKINGS FOR PREFERENTIAL LANES**

|               |  |     |
|---------------|--|-----|
| Section 3D.01 | Preferential Lane Word and Symbol Markings.....                  | 416 |
| Section 3D.02 | Preferential Lane Longitudinal Markings for Motor Vehicles ..... | 417 |

### **CHAPTER 3E. MARKINGS FOR TOLL PLAZAS**

|               |                                |     |
|---------------|--------------------------------|-----|
| Section 3E.01 | Markings for Toll Plazas ..... | 424 |
|---------------|--------------------------------|-----|

**CHAPTER 3F Delineators**

|               |                                       |     |
|---------------|---------------------------------------|-----|
| Section 3F.01 | Delineators .....                     | 425 |
| Section 3F.02 | Delineator Design .....               | 425 |
| Section 3F.03 | Delineator Application .....          | 425 |
| Section 3F.04 | Delineator Placement and Spacing..... | 427 |

**CHAPTER 3G Colored Pavements**

|               |               |     |
|---------------|---------------|-----|
| Section 3G.01 | General ..... | 429 |
|---------------|---------------|-----|

**CHAPTER 3H CHANNELIZING DEVICES USED FOR EMPHASIS OF PAVEMENT MARKING PATTERNS**

|               |                            |     |
|---------------|----------------------------|-----|
| Section 3H.01 | Channelizing Devices ..... | 430 |
|---------------|----------------------------|-----|

**CHAPTER 3I ISLANDS**

|               |                                      |     |
|---------------|--------------------------------------|-----|
| Section 3I.01 | General .....                        | 431 |
| Section 3I.02 | Approach-End Treatment .....         | 431 |
| Section 3I.03 | Island Marking Application .....     | 431 |
| Section 3I.04 | Island Marking Colors .....          | 431 |
| Section 3I.05 | Island Delineation .....             | 432 |
| Section 3I.06 | Pedestrian Islands and Medians ..... | 432 |

**CHAPTER 3J Rumble Strip Markings**

|               |  |     |
|---------------|--|-----|
| Section 3J.01 | Longitudinal Rumble Strip Markings ..... | 433 |
| Section 3J.02 | Transverse Rumble Strip Markings.....    | 433 |

**PART 4 HIGHWAY TRAFFIC SIGNALS**

Rev. 3

**CHAPTER 4A GENERAL**

|               |  |     |
|---------------|--|-----|
| Section 4A.01 | Types .....  | 435 |
| Section 4A.02 | Definitions Relating to Highway Traffic Signals..... | 435 |

**CHAPTER 4B TRAFFIC CONTROL SIGNALS—GENERAL**

|               |  |     |
|---------------|--|-----|
| Section 4B.01 | General .....  | 436 |
| Section 4B.02 | Basis of Installation or Removal of Traffic Control Signals..... | 436 |
| Section 4B.03 | Advantages and Disadvantages of Traffic Control Signals .....    | 436 |
| Section 4B.04 | Alternatives to Traffic Control Signals.....                     | 437 |
| Section 4B.05 | Adequate Roadway Capacity.....                                   | 437 |

**CHAPTER 4C TRAFFIC CONTROL SIGNAL NEEDS STUDIES**

|               |   |     |
|---------------|---|-----|
| Section 4C.01 | Studies and Factors for Justifying Traffic Control Signals..... | 438 |
| Section 4C.02 | Warrant 1, Eight-Hour Vehicular Volume .....                    | 439 |
| Section 4C.03 | Warrant 2, Four-Hour Vehicular Volume .....                     | 441 |
| Section 4C.04 | Warrant 3, Peak Hour .....                                      | 441 |
| Section 4C.05 | Warrant 4, Pedestrian Volume.....                               | 444 |
| Section 4C.06 | Warrant 5, School Crossing.....                                 | 444 |
| Section 4C.07 | Warrant 6, Coordinated Signal System .....                      | 447 |
| Section 4C.08 | Warrant 7, Crash Experience.....                                | 447 |
| Section 4C.09 | Warrant 8, Roadway Network .....                                | 448 |
| Section 4C.10 | Warrant 9, Intersection Near a Grade Crossing.....              | 448 |

**CHAPTER 4D TRAFFIC CONTROL SIGNAL FEATURES**

|               |  |     |
|---------------|--|-----|
| Section 4D.01 | General .....                                      | 451 |
| Section 4D.02 | Responsibility for Operation and Maintenance ..... | 451 |
| Section 4D.03 | Provisions for Pedestrians .....                   | 453 |
| Section 4D.04 | Meaning of Vehicular Signal Indications .....      | 452 |

|               |  |     |
|---------------|--|-----|
| Section 4D.05 | Application of Steady Signal Indications .....   | 455 |
| Section 4D.06 | Signal Indications – Design, Illumination, Color, and Shape.....                                       | 457 |
| Section 4D.07 | Size of Vehicular Signal Indications .....   | 458 |
| Section 4D.08 | Positions of Signal Indications Within a Signal Face – General .....                                   | 459 |
| Section 4D.09 | Positions of Signal Indications Within a Vertical Signal Face .....                                    | 459 |
| Section 4D.10 | Positions of Signal Indications Within a Horizontal Signal Face.....                                   | 461 |
| Section 4D.11 | Number of Signal Faces on an Approach.....   | 461 |
| Section 4D.12 | Visibility, Aiming, and Shielding of Signal Faces.....   | 463 |
| Section 4D.13 | Lateral Positioning of Signal Faces .....  | 465 |
| Section 4D.14 | Longitudinal Positioning of Signal Faces.....  | 466 |
| Section 4D.15 | Mounting Height of Signal Faces .....  | 467 |
| Section 4D.16 | Lateral Offset (Clearance) of Signal Faces.....  | 467 |
| Section 4D.17 | Signal Indications for Left-Turn Movements – General .....   | 467 |
| Section 4D.18 | Signal Indications for Permissive Only Mode Left-Turn Movements .....                                  | 469 |
| Section 4D.19 | Signal Indications for Protected Only Mode Left-Turn Movements .....                                   | 471 |
| Section 4D.20 | Signal Indications for Protected/Permissive Mode Left-Turn Movements.....                              | 473 |
| Section 4D.21 | Signal Indications for Right-Turn Movements – General .....  | 476 |
| Section 4D.22 | Signal Indications for Permissive Only Mode Right-Turn Movements .....                                 | 477 |
| Section 4D.23 | Signal Indications for Protected Only Mode Right-Turn Movements .....                                  | 480 |
| Section 4D.24 | Signal Indications for Protected/Permissive Mode Right-Turn Movements .....                            | 482 |
| Section 4D.25 | Signal Indications for Approaches With Shared Left-Turn/Right-Turn Lanes and No Through Movement ..... | 486 |
| Section 4D.26 | Yellow Change and Red Clearance Intervals .....  | 487 |
| Section 4D.27 | Preemption and Priority Control of Traffic Control Signals .....                                       | 491 |
| Section 4D.28 | Flashing Operation of Traffic Control Signals – General .....  | 493 |
| Section 4D.29 | Flashing Operation – Transition Into Flashing Mode .....   | 493 |
| Section 4D.30 | Flashing Operation – Signal Indications During Flashing Mode .....                                     | 493 |
| Section 4D.31 | Flashing Operation – Transition Out of Flashing Mode .....   | 494 |
| Section 4D.32 | Temporary and Portable Traffic Control Signals .....   | 494 |
| Section 4D.33 | Lateral Offset of Signal Supports and Cabinets .....   | 495 |
| Section 4D.34 | Use of Signs at Signalized Locations .....   | 495 |
| Section 4D.35 | Use of Pavement Markings at Signalized Locations .....   | 496 |

Rev. 3

## **CHAPTER 4E PEDESTRIAN CONTROL FEATURES**

|               |  |     |
|---------------|--|-----|
| Section 4E.01 | Pedestrian Signal Heads .....  | 497 |
| Section 4E.02 | Meaning of Pedestrian Signal Head Indications .....                                    | 497 |
| Section 4E.03 | Application of Pedestrian Signal Heads .....   | 497 |
| Section 4E.04 | Size, Design, and Illumination of Pedestrian Signal Head Indications .....             | 498 |
| Section 4E.05 | Location and Height of Pedestrian Signal Heads .....                                   | 499 |
| Section 4E.06 | Pedestrian Intervals and Signal Phases .....   | 499 |
| Section 4E.07 | Countdown Pedestrian Signals .....   | 501 |
| Section 4E.08 | Pedestrian Detectors .....   | 502 |
| Section 4E.09 | Accessible Pedestrian Signals and Detectors – General .....                            | 506 |
| Section 4E.10 | Accessible Pedestrian Signals and Detectors – Location .....                           | 507 |
| Section 4E.11 | Accessible Pedestrian Signals and Detectors – Walk Indications .....                   | 507 |
| Section 4E.12 | Accessible Pedestrian Signals and Detectors – Tactile Arrows and Locator Tones .....   | 509 |
| Section 4E.13 | Accessible Pedestrian Signals and Detectors – Extended Pushbutton Press Features ..... | 509 |

## **CHAPTER 4F PEDESTRIAN HYBRID BEACONS**

|               |  |     |
|---------------|--|-----|
| Section 4F.01 | Application of Pedestrian Hybrid Beacons ..... | 511 |
| Section 4F.02 | Design of Pedestrian Hybrid Beacons .....      | 511 |
| Section 4F.03 | Operation of Pedestrian Hybrid Beacons .....   | 513 |

## **CHAPTER 4G TRAFFIC CONTROL SIGNALS AND HYBRID BEACONS FOR EMERGENCY-VEHICLE ACCESS**

|               |   |     |
|---------------|---|-----|
| Section 4G.01 | Application of Emergency-Vehicle Traffic Control Signals and Hybrid Beacons ..... | 515 |
| Section 4G.02 | Design of Emergency-Vehicle Traffic Control Signals .....                         | 515 |
| Section 4G.03 | Operation of Emergency-Vehicle Traffic Control Signals .....                      | 515 |
| Section 4G.04 | Emergency-Vehicle Hybrid Beacons .....  | 516 |

## **CHAPTER 4H TRAFFIC CONTROL SIGNALS FOR ONE-LANE, TWO-WAY FACILITIES**

|               |   |     |
|---------------|---|-----|
| Section 4H.01 | Application of Traffic Control Signals for One-Lane, Two-Way Facilities ..... | 518 |
| Section 4H.02 | Design of Traffic Control Signals for One-Lane, Two-Way Facilities .....      | 518 |
| Section 4H.03 | Operation of Traffic Control Signals for One-Lane, Two-Way Facilities .....   | 518 |

## **CHAPTER 4I TRAFFIC CONTROL SIGNALS FOR FREEWAY ENTRANCE RAMPS**

|               |   |     |
|---------------|---|-----|
| Section 4I.01 | Application of Freeway Entrance Ramp Control Signals..... | 519 |
| Section 4I.02 | Design of Freeway Entrance Ramp Control Signals .....     | 519 |
| Section 4I.03 | Operation of Freeway Entrance Ramp Control Signals .....  | 520 |

## **CHAPTER 4J TRAFFIC CONTROL FOR MOBILE BRIDGES**

|               |   |     |
|---------------|---|-----|
| Section 4J.01 | Application of Traffic Control for Movable Bridges .....      | 521 |
| Section 4J.02 | Design and Location of Movable Bridge Signals and Gates ..... | 521 |
| Section 4J.03 | Operation of Movable Bridge Signals and Gates .....           | 523 |

## **CHAPTER 4K HIGHWAY TRAFFIC SIGNALS AT TOLL PLAZAS**

|               |   |     |
|---------------|---|-----|
| Section 4K.01 | Traffic Signals at Toll Plazas .....                  | 524 |
| Section 4K.02 | Lane-Use Control Signals at or Near Toll Plazas ..... | 524 |
| Section 4K.03 | Warning Beacons at Toll Plazas .....                  | 524 |

## **CHAPTER 4L FLASHING BEACONS**

|               |  |     |
|---------------|--|-----|
| Section 4L.01 | General Design and Operation of Flashing Beacons ..... | 525 |
| Section 4L.02 | Intersection Control Beacon.....                       | 525 |
| Section 4L.03 | Warning Beacon.....                                    | 525 |
| Section 4L.04 | Speed Limit Sign Beacon.....                           | 526 |
| Section 4L.05 | Stop Beacon .....                                      | 526 |

## **CHAPTER 4M LANE-USE CONTROL SIGNALS**

|               |   |     |
|---------------|---|-----|
| Section 4M.01 | Application of Lane-Use Control Signals .....       | 527 |
| Section 4M.02 | Meaning of Lane-Use Control Signal Indications..... | 527 |
| Section 4M.03 | Design of Lane-Use Control Signals .....            | 528 |
| Section 4M.04 | Operation of Lane-Use Control Signals .....         | 529 |

## **CHAPTER 4N IN-ROADWAY LIGHTS**

|               |   |     |
|---------------|---|-----|
| Section 4N.01 | Application of In-Roadway Lights .....        | 530 |
| Section 4N.02 | In-Roadway Warning Lights at Crosswalks ..... | 530 |

# **PART 5 TRAFFIC CONTROL DEVICES FOR LOW-VOLUME ROADS**

## **CHAPTER 5A GENERAL**

|               |                   |     |
|---------------|-------------------|-----|
| Section 5A.01 | Function .....    | 533 |
| Section 5A.02 | Application ..... | 533 |
| Section 5A.03 | Design .....      | 533 |
| Section 5A.04 | Placement .....   | 535 |

## **CHAPTER 5B REGULATORY SIGNS**

|               |  |     |
|---------------|--|-----|
| Section 5B.01 | Introduction .....                         | 536 |
| Section 5B.02 | STOP and YIELD Signs (R1-1 and R1-2) ..... | 536 |

|               |   |     |
|---------------|---|-----|
| Section 5B.03 | Speed Limit Signs (R2 Series) .....   | 536 |
| Section 5B.04 | Traffic Movement and Prohibition Signs (R3, R4, R5, R6, R9, R10, R11, R12, R13, and R14 Series) ..... | 537 |
| Section 5B.05 | Parking Signs (R8 Series) .....   | 537 |
| Section 5B.06 | Other Regulatory Signs .....  | 537 |

## **CHAPTER 5C WARNING SIGNS**

|               |   |     |
|---------------|---|-----|
| Section 5C.01 | Introduction .....  | 538 |
| Section 5C.02 | Horizontal Alignment Signs (W1-1 through W1-8) .....                                  | 538 |
| Section 5C.03 | Intersection Warning Signs (W2-1 through W2-6) .....                                  | 539 |
| Section 5C.04 | Stop Ahead and Yield Ahead Signs (W3-1, W3-2) .....                                   | 539 |
| Section 5C.05 | NARROW BRIDGE Sign (W5-2) .....   | 539 |
| Section 5C.06 | ONE LANE BRIDGE Sign (W5-3) .....   | 539 |
| Section 5C.07 | Hill Sign (W7-1) .....  | 539 |
| Section 5C.08 | PAVEMENT ENDS Sign (W8-3) .....   | 539 |
| Section 5C.09 | Vehicular Traffic Warning and Non-Vehicular Warning Signs (W11 Series and W8-6) ..... | 539 |
| Section 5C.10 | Advisory Speed Plaque (W13-1P) .....  | 541 |
| Section 5C.11 | DEAD END or NO OUTLET Signs (W14-1, W14-1a, W14-2, W14-2a) .....                      | 541 |
| Section 5C.12 | NO TRAFFIC SIGNS Sign (W18-1).....  | 541 |
| Section 5C.13 | Other Warning Signs.....  | 541 |
| Section 5C.14 | Object Markers and Barricades.....  | 541 |

## **CHAPTER 5D GUIDE SIGNS**

|               |                    |     |
|---------------|--------------------|-----|
| Section 5D.01 | Introduction ..... | 542 |
|---------------|--------------------|-----|

Rev. 3

## **CHAPTER 5E MARKINGS**

|               |                            |     |
|---------------|----------------------------|-----|
| Section 5E.01 | Introduction .....         | 543 |
| Section 5E.02 | Center Line Markings ..... | 543 |
| Section 5E.03 | Edge Line Markings.....    | 543 |
| Section 5E.04 | Delineators .....          | 543 |
| Section 5E.05 | Other Markings .....       | 543 |

## **CHAPTER 5F TRAFFIC CONTROL FOR HIGHWAY-RAIL GRADE CROSSINGS**

|               |   |     |
|---------------|---|-----|
| Section 5F.01 | Introduction .....  | 544 |
| Section 5F.02 | Grade Crossing (Crossbuck) Sign and Number of Tracks Plaque (R15-1, R15-2P) ..... | 544 |
| Section 5F.03 | Grade Crossing Advance Warning Signs (W10 Series) .....                           | 544 |
| Section 5F.04 | STOP and YIELD Signs (R1-1, R1-2) .....   | 545 |
| Section 5F.05 | Pavement Markings .....   | 545 |
| Section 5F.06 | Other Traffic Control Devices .....   | 545 |

## **CHAPTER 5G TEMPORARY TRAFFIC CONTROL ZONES**

|               |                                     |     |
|---------------|-------------------------------------|-----|
| Section 5G.01 | Introduction .....                  | 546 |
| Section 5G.02 | Applications .....                  | 546 |
| Section 5G.03 | Channelization Devices.....         | 546 |
| Section 5G.04 | Markings .....                      | 547 |
| Section 5G.05 | Other Traffic Control Devices ..... | 547 |

## **CHAPTER 5H TRAFFIC CONTROL FOR SCHOOL AREAS**

|               |                    |     |
|---------------|--------------------|-----|
| Section 5H.01 | Introduction ..... | 548 |
|---------------|--------------------|-----|

**PART 6 TEMPORARY TRAFFIC CONTROL****CHAPTER 6A GENERAL**

|               |               |     |
|---------------|---------------|-----|
| Section 6A.01 | General ..... | 549 |
|---------------|---------------|-----|

**CHAPTER 6B FUNDAMENTAL PRINCIPLES**

|               |   |     |
|---------------|---|-----|
| Section 6B.01 | Fundamental Principles of Temporary Traffic Control ..... | 551 |
|---------------|---|-----|

**CHAPTER 6C TEMPORARY TRAFFIC CONTROL ELEMENTS**

|               |   |     |
|---------------|---|-----|
| Section 6C.01 | Temporary Traffic Control Plans.....  | 553 |
| Section 6C.02 | Temporary Traffic Control Zones .....   | 554 |
| Section 6C.03 | Components of Temporary Traffic Control Zones .....                               | 554 |
| Section 6C.04 | Advance Warning Area .....  | 554 |
| Section 6C.05 | Transition Area.....  | 556 |
| Section 6C.06 | Activity Area.....  | 556 |
| Section 6C.07 | Termination Area .....  | 557 |
| Section 6C.08 | Tapers .....  | 557 |
| Section 6C.09 | Detours and Diversions .....  | 560 |
| Section 6C.10 | One-Lane, Two-Way Traffic Control.....  | 560 |
| Section 6C.11 | Flagger Method of One-Lane, Two-Way Traffic Control .....                         | 560 |
| Section 6C.12 | Flag Transfer Method of One-Lane, Two-Way Traffic Control .....                   | 560 |
| Section 6C.13 | Pilot Car Method of One-Lane, Two-Way Traffic Control.....                        | 562 |
| Section 6C.14 | Temporary Traffic Control Signal Method of One-Lane, Two-Way Traffic Control..... | 562 |
| Section 6C.15 | Stop or Yield Control Method of One-Lane, Two-Way Traffic Control .....           | 562 |

**CHAPTER 6D PEDESTRIAN AND WORKER SAFETY**

|               |                                    |     |
|---------------|------------------------------------|-----|
| Section 6D.01 | Pedestrian Considerations .....    | 563 |
| Section 6D.02 | Accessibility Considerations ..... | 565 |
| Section 6D.03 | Worker Safety Considerations ..... | 566 |

**CHAPTER 6E FLAGGER CONTROL**

|               |  |     |
|---------------|--|-----|
| Section 6E.01 | Qualifications for Flaggers .....                          | 568 |
| Section 6E.02 | High-Visibility Safety Apparel .....                       | 568 |
| Section 6E.03 | Hand-Signaling Devices.....                                | 568 |
| Section 6E.04 | Automated Flagger Assistance Devices .....                 | 569 |
| Section 6E.05 | STOP/SLOW Automated Flagger Assistance Devices .....       | 570 |
| Section 6E.06 | Red/Yellow Lens Automated Flagger Assistance Devices ..... | 573 |
| Section 6E.07 | Flagger Procedures .....                                   | 575 |
| Section 6E.08 | Flagger Stations.....                                      | 577 |

**CHAPTER 6F TEMPORARY TRAFFIC CONTROL ZONE DEVICES**

|               |  |     |
|---------------|--|-----|
| Section 6F.01 | Types of Devices .....                                   | 578 |
| Section 6F.02 | General Characteristics of Signs .....                   | 578 |
| Section 6F.03 | Sign Placement .....                                     | 579 |
| Section 6F.04 | Sign Maintenance.....                                    | 585 |
| Section 6F.05 | Regulatory Sign Authority .....                          | 585 |
| Section 6F.06 | Regulatory Sign Design .....                             | 585 |
| Section 6F.07 | Regulatory Sign Applications .....                       | 585 |
| Section 6F.08 | ROAD (STREET) CLOSED Sign (R11-2) .....                  | 585 |
| Section 6F.09 | Local Traffic Only Signs (R11-3a, R11-4) .....           | 587 |
| Section 6F.10 | Weight Limit Signs (R12-1, R12-2, R12-5) .....           | 587 |
| Section 6F.11 | STAY IN LANE Sign (R4-9).....                            | 588 |
| Section 6F.12 | Work Zone and Higher Fines Signs and Plaques .....       | 588 |
| Section 6F.13 | PEDESTRIAN CROSSWALK Sign (R9-8) .....                   | 588 |
| Section 6F.14 | SIDEWALK CLOSED Signs (R9-9, R9-10, R9-11, R9-11a) ..... | 588 |

|               |   |     |
|---------------|---|-----|
| Section 6F.15 | Special Regulatory Signs .....  | 589 |
| Section 6F.16 | Warning Sign Function, Design, and Application.....                           | 589 |
| Section 6F.17 | Position of Advance Warning Signs.....  | 589 |
| Section 6F.18 | ROAD (STREET) WORK Sign (W20-1).....  | 593 |
| Section 6F.19 | DETOUR Sign (W20-2) .....   | 593 |
| Section 6F.20 | ROAD (STREET) CLOSED Sign (W20-3) .....                                       | 593 |
| Section 6F.21 | ONE LANE ROAD Sign (W20-4) .....  | 593 |
| Section 6F.22 | Lane(s) Closed Signs (W20-5, W20-5a) .....                                    | 593 |
| Section 6F.23 | CENTER LANE CLOSED AHEAD Sign (W9-3).....                                     | 594 |
| Section 6F.24 | Lane Ends Sign (W4-2) .....   | 594 |
| Section 6F.25 | ON RAMP Plaque (W13-4P) .....   | 594 |
| Section 6F.26 | RAMP NARROWS Sign (W5-4) .....  | 594 |
| Section 6F.27 | SLOW TRAFFIC AHEAD Sign (W23-1) .....   | 594 |
| Section 6F.28 | EXIT OPEN and EXIT CLOSED Signs (E5-2, E5-2a) .....                           | 594 |
| Section 6F.29 | EXIT ONLY Sign (E5-3) .....   | 595 |
| Section 6F.30 | NEW TRAFFIC PATTERN AHEAD Sign (W23-2) .....                                  | 595 |
| Section 6F.31 | Flagger Signs (W20-7, W20-7a) .....   | 595 |
| Section 6F.32 | Two-Way Traffic Sign (W6-3) .....   | 595 |
| Section 6F.33 | Workers Signs (W21-1, W21-1a) .....   | 595 |
| Section 6F.34 | FRESH OIL (TAR) Sign (W21-2) .....  | 595 |
| Section 6F.35 | ROAD MACHINERY AHEAD Sign (W21-3) .....                                       | 595 |
| Section 6F.36 | Motorized Traffic Signs (W8-6, W11-10).....                                   | 596 |
| Section 6F.37 | Shoulder Work Signs (W21-5, W21-5a, W21-5b) .....                             | 596 |
| Section 6F.38 | SURVEY CREW Sign (W21-6) .....  | 596 |
| Section 6F.39 | UTILITY WORK Sign (W21-7) .....   | 596 |
| Section 6F.40 | Signs for Blasting Areas.....   | 596 |
| Section 6F.41 | BLASTING ZONE AHEAD Sign (W22-1).....   | 597 |
| Section 6F.42 | TURN OFF 2-WAY RADIO AND CELL PHONE Sign (W22-2) .....                        | 597 |
| Section 6F.43 | END BLASTING ZONE Sign (W22-3) .....  | 597 |
| Section 6F.44 | Shoulder Signs and Plaque (W8-4, W8-9, W8-17, and W8-17P) .....               | 597 |
| Section 6F.45 | UNEVEN LANES Sign (W8-11) .....   | 597 |
| Section 6F.46 | STEEL PLATE AHEAD Sign (W8-24) .....  | 597 |
| Section 6F.47 | NO CENTER LINE Sign (W8-12) .....   | 597 |
| Section 6F.48 | Reverse Curve Signs (W1-4 Series) .....                                       | 598 |
| Section 6F.49 | Double Reverse Curve Signs (W24-1 Series) .....                               | 598 |
| Section 6F.50 | Other Warning Signs.....  | 598 |
| Section 6F.51 | Special Warning Signs .....   | 598 |
| Section 6F.52 | Advisory Speed Plaque (W13-1P) .....  | 598 |
| Section 6F.53 | Supplementary Distance Plaque (W7-3aP) .....                                  | 599 |
| Section 6F.54 | Motorcycle Plaque (W8-15P) .....  | 599 |
| Section 6F.55 | Guide Signs .....   | 599 |
| Section 6F.56 | ROAD WORK NEXT XX MILES Sign (G20-1) .....                                    | 599 |
| Section 6F.57 | END ROAD WORK Sign (G20-2).....   | 600 |
| Section 6F.58 | PILOT CAR FOLLOW ME Sign (G20-4).....   | 600 |
| Section 6F.59 | Detour Signs (M4-8, M4-8a, M4-8b, M4-9, M4-9a, M4-9b, M4-9c, and M4-10) ..... | 600 |
| Section 6F.60 | Portable Changeable Message Signs .....                                       | 600 |
| Section 6F.61 | Arrow Boards .....  | 603 |
| Section 6F.62 | High-Level Warning Devices (Flag Trees) .....                                 | 605 |
| Section 6F.63 | Channelizing Devices .....  | 606 |
| Section 6F.64 | Cones.....  | 608 |
| Section 6F.65 | Tubular Markers .....   | 608 |
| Section 6F.66 | Vertical Panels.....  | 609 |
| Section 6F.67 | Drums .....   | 609 |

Rev. 3

|               |  |     |
|---------------|--|-----|
| Section 6F.68 | Type 1, 2, or 3 Barricades .....                         | 611 |
| Section 6F.69 | Direction Indicator Barricades .....                     | 611 |
| Section 6F.70 | Temporary Traffic Barriers as Channelizing Devices ..... | 611 |
| Section 6F.71 | Longitudinal Channelizing Devices .....                  | 611 |
| Section 6F.72 | Temporary Lane Separators .....                          | 612 |
| Section 6F.73 | Other Channelizing Devices .....                         | 612 |
| Section 6F.74 | Detectable Edging for Pedestrians .....                  | 612 |
| Section 6F.75 | Temporary Raised Islands .....                           | 613 |
| Section 6F.76 | Opposing Traffic Lane Divider and Sign (W6-4) .....      | 613 |
| Section 6F.77 | Pavement Markings .....                                  | 614 |
| Section 6F.78 | Temporary Markings .....                                 | 614 |
| Section 6F.79 | Temporary Raised Pavement Markers .....                  | 615 |
| Section 6F.80 | Delineators .....  | 615 |
| Section 6F.81 | Lighting Devices .....                                   | 616 |
| Section 6F.82 | Floodlights .....  | 616 |
| Section 6F.83 | Warning Lights .....                                     | 616 |
| Section 6F.84 | Temporary Traffic Control Signals .....                  | 617 |
| Section 6F.85 | Temporary Traffic Barriers .....                         | 618 |
| Section 6F.86 | Crash Cushions .....                                     | 619 |
| Section 6F.87 | Rumble Strips .....                                      | 620 |
| Section 6F.88 | Screens .....  | 620 |

## **CHAPTER 6G TYPE OF TEMPORARY TRAFFIC CONTROL ZONE ACTIVITIES**

|               |   |     |
|---------------|---|-----|
| Section 6G.01 | Typical Applications .....  | 621 |
| Section 6G.02 | Work Duration .....   | 621 |
| Section 6G.03 | Location of Work .....  | 623 |
| Section 6G.04 | Modifications To Fulfill Special Needs .....                                      | 623 |
| Section 6G.05 | Work Affecting Pedestrian and Bicycle Facilities .....                            | 624 |
| Section 6G.06 | Work Outside of the Shoulder .....  | 624 |
| Section 6G.07 | Work on the Shoulder with No Encroachment .....                                   | 625 |
| Section 6G.08 | Work on the Shoulder with Minor Encroachment .....                                | 626 |
| Section 6G.09 | Work Within the Median .....  | 626 |
| Section 6G.10 | Work Within the Traveled Way of a Two-Lane Highway .....                          | 626 |
| Section 6G.11 | Work Within the Traveled Way of an Urban Street .....                             | 627 |
| Section 6G.12 | Work Within the Traveled Way of a Multi-Lane, Non-Access Controlled Highway ..... | 627 |
| Section 6G.13 | Work Within the Traveled Way at an Intersection .....                             | 628 |
| Section 6G.14 | Work Within the Traveled Way of a Freeway or Expressway .....                     | 629 |
| Section 6G.15 | Two-Lane, Two-Way Traffic on One Roadway of a Normally Divided Highway .....      | 630 |
| Section 6G.16 | Crossovers .....  | 630 |
| Section 6G.17 | Interchanges .....  | 630 |
| Section 6G.18 | Work in the Vicinity of a Grade Crossing .....                                    | 631 |
| Section 6G.19 | Temporary Traffic Control During Nighttime Hours .....                            | 631 |

## **CHAPTER 6H TYPICAL APPLICATIONS**

|               |                            |     |
|---------------|----------------------------|-----|
| Section 6H.01 | Typical Applications ..... | 633 |
|---------------|----------------------------|-----|

## **CHAPTER 6I CONTROL OF TRAFFIC THROUGH TRAFFIC INCIDENT MANAGEMENT AREAS**

|               |   |     |
|---------------|---|-----|
| Section 6I.01 | General .....                           | 728 |
| Section 6I.02 | Major Traffic Incidents .....           | 729 |
| Section 6I.03 | Intermediate Traffic Incidents .....    | 730 |
| Section 6I.04 | Minor Traffic Incidents .....           | 730 |
| Section 6I.05 | Use of Emergency-Vehicle Lighting ..... | 731 |

**PART 7 TRAFFIC CONTROL FOR SCHOOL AREAS****CHAPTER 7A GENERAL**

|               |  |     |
|---------------|--|-----|
| Section 7A.01 | Need for Standards.....                              | 733 |
| Section 7A.02 | School Routes and Established School Crossings ..... | 733 |
| Section 7A.03 | School Crossing Control Criteria .....               | 733 |
| Section 7A.04 | Scope .....  | 734 |

**CHAPTER 7B SIGNS**

|               |  |     |
|---------------|--|-----|
| Section 7B.01 | Size of School Signs .....   | 735 |
| Section 7B.02 | Illumination and Reflectorization.....   | 736 |
| Section 7B.03 | Position of Signs .....  | 736 |
| Section 7B.04 | Height of Signs .....  | 736 |
| Section 7B.05 | Installation of Signs.....   | 736 |
| Section 7B.06 | Lettering.....   | 736 |
| Section 7B.07 | Sign Color for School Warning Signs .....  | 736 |
| Section 7B.08 | School Sign (S1-1) and Plaques .....   | 736 |
| Section 7B.09 | School Zone Sign (S1-1) and Plaques (S4-3P, S4-7P) and END SCHOOL ZONE Sign (S5-2).....                            | 738 |
| Section 7B.10 | Higher Fines Zone Signs (R2-10, R2-11) and Plaques .....   | 738 |
| Section 7B.11 | School Advance Crossing Assembly .....   | 738 |
| Section 7B.12 | School Crossing Assembly .....   | 743 |
| Section 7B.13 | School Bus Stop Ahead Sign (S3-1) .....  | 744 |
| Section 7B.14 | SCHOOL BUS TURN AHEAD Sign (S3-2) .....  | 744 |
| Section 7B.15 | School Speed Limit Assembly (S4-1P, S4-2P, S4-3P, S4-4P, S4-6P, S5-1) and END SCHOOL SPEED LIMIT Sign (S5-3) ..... | 744 |
| Section 7B.16 | Reduced School Speed Limit Ahead Sign (S4-5, S4-5a).....   | 745 |
| Section 7B.17 | Parking and Stopping Signs (R7 and R8 Series) .....  | 745 |

Rev. 3

**CHAPTER 7C MARKINGS**

|               |  |     |
|---------------|--|-----|
| Section 7C.01 | Functions and Limitations.....                 | 746 |
| Section 7C.02 | Crosswalk Markings .....                       | 746 |
| Section 7C.03 | Pavement Word, Symbol, and Arrow Markings..... | 746 |

**CHAPTER 7D CROSSING SUPERVISION**

|               |  |     |
|---------------|--|-----|
| Section 7D.01 | Types of Crossing Supervision .....                  | 747 |
| Section 7D.02 | Adult Crossing Guards .....                          | 747 |
| Section 7D.03 | Qualifications of Adult Crossing Guards .....        | 747 |
| Section 7D.04 | Uniform of Adult Crossing Guards .....               | 747 |
| Section 7D.05 | Operating Procedures for Adult Crossing Guards ..... | 747 |

**PART 8 TRAFFIC CONTROL FOR RAILROAD AND LIGHT RAIL TRANSIT GRADE CROSSINGS****CHAPTER 8A GENERAL**

|               |   |     |
|---------------|---|-----|
| Section 8A.01 | Introduction .....  | 749 |
| Section 8A.02 | Use of Standard Devices, Systems, and Practices at Highway-Rail Grade Crossings ..... | 749 |
| Section 8A.03 | Use of Standard Devices, Systems, and Practices at Highway-LRT Grade Crossings .....  | 750 |
| Section 8A.04 | Uniform Provisions .....  | 751 |
| Section 8A.05 | Grade Crossing Elimination.....   | 751 |
| Section 8A.06 | Illumination at Grade Crossings .....   | 752 |
| Section 8A.07 | Quiet Zone Treatments at Highway-Rail Grade Crossings .....                           | 752 |
| Section 8A.08 | Temporary Traffic Control Zones .....   | 752 |

**CHAPTER 8B SIGNS AND MARKINGS**

|               |  |     |
|---------------|--|-----|
| Section 8B.01 | Purpose .....  | 753 |
| Section 8B.02 | Sizes of Grade Crossing Signs .....  | 753 |
| Section 8B.03 | Grade Crossing (Crossbuck) Sign (R15-1) and Number of Tracks Plaque (R15-2P) at Active and Passive Grade Crossings ..... | 753 |
| Section 8B.04 | Crossbuck Assemblies with YIELD or STOP Signs at Passive Grade Crossings .....   | 756 |
| Section 8B.05 | Use of STOP (R1-1) or YIELD (R1-2) Signs without Crossbuck Signs at Highway-LRT Grade Crossings .....                    | 760 |
| Section 8B.06 | Grade Crossing Advance Warning Signs (W10 Series) .....  | 760 |
| Section 8B.07 | EXEMPT Grade Crossing Plaques (R15-3P, W10-1aP) .....  | 761 |
| Section 8B.08 | Turn Restrictions During Preemption .....  | 762 |
| Section 8B.09 | DO NOT STOP ON TRACKS Sign (R8-8) .....  | 762 |
| Section 8B.10 | TRACKS OUT OF SERVICE Sign (R8-9) .....  | 762 |
| Section 8B.11 | STOP HERE WHEN FLASHING Signs (R8-10, R8-10a) .....  | 763 |
| Section 8B.12 | STOP HERE ON RED Signs (R10-6, R10-6a) .....   | 763 |
| Section 8B.13 | Light Rail Transit Only Lane Signs (R15-4 Series) .....  | 763 |
| Section 8B.14 | Do Not Pass Light Rail Transit Signs (R15-5, R15-5a) .....   | 763 |
| Section 8B.15 | No Motor Vehicles On Tracks Signs (R15-6, R15-6a) .....  | 764 |
| Section 8B.16 | Divided Highway with Light Rail Transit Crossing Signs (R15-7 Series) .....  | 764 |
| Section 8B.17 | LOOK Sign (R15-8) .....  | 764 |
| Section 8B.18 | Emergency Notification Sign (I-13) .....   | 764 |
| Section 8B.19 | Light Rail Transit Approaching-Activated Blank-Out Warning Sign (W10-7) .....  | 765 |
| Section 8B.20 | TRAIN MAY EXCEED 80 MPH Sign (W10-8) .....   | 765 |
| Section 8B.21 | NO TRAIN HORN Sign or Plaque (W10-9, W10-9P) .....   | 765 |
| Section 8B.22 | NO GATES OR LIGHTS Plaque (W10-13P) .....  | 765 |
| Section 8B.23 | Low Ground Clearance Grade Crossing Sign (W10-5) .....   | 765 |
| Section 8B.24 | Storage Space Signs (W10-11, W10-11a, W10-11b) .....   | 766 |
| Section 8B.25 | Skewed Crossing Sign (W10-12) .....  | 766 |
| Section 8B.26 | Light Rail Transit Station Sign (I-12) .....   | 766 |
| Section 8B.27 | Pavement Markings .....  | 766 |
| Section 8B.28 | Stop and Yield Lines .....   | 768 |
| Section 8B.29 | Dynamic Envelope Markings .....  | 769 |

**CHAPTER 8C FLASHING-LIGHT SIGNALS, GATES, AND TRAFFIC CONTROL SIGNALS**

|               |   |     |
|---------------|---|-----|
| Section 8C.01 | Introduction .....  | 771 |
| Section 8C.02 | Flashing-Light Signals .....  | 771 |
| Section 8C.03 | Flashing-Light Signals at Highway-LRT Grade Crossings .....                         | 773 |
| Section 8C.04 | Automatic Gates .....   | 774 |
| Section 8C.05 | Use of Automatic Gates at LRT Grade Crossings .....                                 | 775 |
| Section 8C.06 | Four-Quadrant Gate Systems .....  | 775 |
| Section 8C.07 | Wayside Horn Systems .....  | 777 |
| Section 8C.08 | Rail Traffic Detection .....  | 777 |
| Section 8C.09 | Traffic Control Signals at or Near Highway-Rail Grade Crossings .....               | 778 |
| Section 8C.10 | Traffic Control Signals at or Near Highway-LRT Grade Crossings .....                | 779 |
| Section 8C.11 | Use of Traffic Control Signals for Control of LRT Vehicles at Grade Crossings ..... | 780 |
| Section 8C.12 | Grade Crossings Within or In Close Proximity to Circular Intersections .....        | 782 |
| Section 8C.13 | Pedestrian and Bicycle Signals and Crossings at LRT Grade Crossings .....           | 782 |

**CHAPTER 8D PATHWAY GRADE CROSSINGS**

|               |  |     |
|---------------|--|-----|
| Section 8D.01 | Purpose .....  | 788 |
| Section 8D.02 | Use of Standard Devices, Systems, and Practices .....            | 788 |
| Section 8D.03 | Pathway Grade Crossing Signs and Markings .....                  | 788 |
| Section 8D.04 | Stop Lines, Edge Lines, and Detectable Warnings .....            | 788 |
| Section 8D.05 | Passive Devices for Pathway Grade Crossings .....                | 789 |
| Section 8D.06 | Active Traffic Control Systems for Pathway Grade Crossings ..... | 790 |

**PART 9 TRAFFIC CONTROL FOR BICYCLE FACILITIES****CHAPTER 9A GENERAL**

|               |  |     |
|---------------|--|-----|
| Section 9A.01 | Requirements for Bicyclist Traffic Control Devices ..... | 791 |
| Section 9A.02 | Scope .....  | 791 |
| Section 9A.03 | Definitions Relating to Bicycles .....                   | 791 |
| Section 9A.04 | Maintenance .....  | 791 |
| Section 9A.05 | Relation to Other Documents .....                        | 791 |
| Section 9A.06 | Placement Authority .....                                | 791 |
| Section 9A.07 | Meaning of Standard, Guidance, Option, and Support ..... | 791 |
| Section 9A.08 | Colors .....   | 791 |

**CHAPTER 9B SIGNS**

|               |  |     |
|---------------|--|-----|
| Section 9B.01 | Application and Placement of Signs .....   | 792 |
| Section 9B.02 | Design of Bicycle Signs .....  | 792 |
| Section 9B.03 | STOP and YIELD Signs (R1-1, R1-2) .....  | 794 |
| Section 9B.04 | Bike Lane Signs and Plaques (R3-17, R3-17aP, R3-17bP) .....  | 796 |
| Section 9B.05 | BEGIN RIGHT TURN LANE YIELD TO BIKES Sign (R4-4) .....   | 796 |
| Section 9B.06 | Bicycles May Use Full Lane Sign (R4-11) .....  | 796 |
| Section 9B.07 | Bicycle WRONG WAY Sign and RIDE WITH TRAFFIC Plaque (R5-1b, R9-3cP) .....  | 796 |
| Section 9B.08 | NO MOTOR VEHICLES Sign (R5-3) .....  | 797 |
| Section 9B.09 | Selective Exclusion Signs .....  | 797 |
| Section 9B.10 | No Parking Bike Lane Signs (R7-9, R7-9a) .....   | 797 |
| Section 9B.11 | Bicycle Regulatory Signs (R9-5, R9-6, R10-4, R10-24, R10-25, and R10-26) .....   | 797 |
| Section 9B.12 | Shared-Use Path Restriction Sign (R9-7) .....  | 797 |
| Section 9B.13 | Bicycle Signal Actuation Sign (R10-22) .....   | 798 |
| Section 9B.14 | Other Regulatory Signs .....   | 798 |
| Section 9B.15 | Turn or Curve Warning Signs (W1 Series) .....  | 798 |
| Section 9B.16 | Intersection Warning Signs (W2 Series) .....   | 798 |
| Section 9B.17 | Bicycle Surface Condition Warning Sign (W8-10) .....   | 798 |
| Section 9B.18 | Bicycle Warning and Combined Bicycle/Pedestrian Signs (W11-1 and W11-15) .....   | 798 |
| Section 9B.19 | Other Bicycle Warning Signs .....  | 800 |
| Section 9B.20 | Bicycle Guide Signs (D1-1b, D1-1c, D1-2b, D1-2c, D1-3b, D1-3c, D11-1, D11-1c) .....                                    | 800 |
| Section 9B.21 | Bicycle Route Signs (M1-8, M1-8a, M1-9) .....  | 802 |
| Section 9B.22 | Bicycle Route Sign Auxiliary Plaques .....   | 804 |
| Section 9B.23 | Bicycle Parking Area Sign (D4-3) .....   | 806 |
| Section 9B.24 | Reference Location Signs (D10-1 through D10-3) and Intermediate Reference Location Signs (D10-1a through D10-3a) ..... | 806 |
| Section 9B.25 | Mode-Specific Guide Signs for Shared-Use Paths (D11-1a, D11-2, D11-3, D11-4) .....                                     | 807 |
| Section 9B.26 | Object Markers .....   | 807 |

**CHAPTER 9C MARKINGS**

|               |   |     |
|---------------|---|-----|
| Section 9C.01 | Functions of Markings .....                           | 808 |
| Section 9C.02 | General Principles .....                              | 808 |
| Section 9C.03 | Marking Patterns and Colors on Shared-Use Paths ..... | 808 |
| Section 9C.04 | Markings For Bicycle Lanes .....                      | 808 |
| Section 9C.05 | Bicycle Detector Symbol .....                         | 812 |
| Section 9C.06 | Pavement Markings for Obstructions .....              | 812 |
| Section 9C.07 | Shared Lane Marking .....                             | 812 |

**CHAPTER 9D SIGNALS**

|               |                                      |     |
|---------------|--------------------------------------|-----|
| Section 9D.01 | Application .....                    | 818 |
| Section 9D.02 | Signal Operations for Bicycles ..... | 818 |

|              |  |     |
|--------------|--|-----|
| Figure 2M-2  | Examples of Recreational and Cultural Interest Area Guide Signs .....  | 334 |
| Figure 2M-3  | Arrangement, Height, and Lateral Position of Signs Located Within Recreational and Cultural Interest Areas ..... | 335 |
| Figure 2M-4  | Examples of Symbol and Destination Guide Signing Layout .....  | 336 |
| Figure 2M-5  | Recreational and Cultural Interest Area Symbol Signs for General Applications .....                              | 337 |
| Figure 2M-6  | Recreational and Cultural Interest Area Symbol Signs for Accommodations .....                                    | 338 |
| Figure 2M-7  | Recreational and Cultural Interest Area Symbol Signs for Services.....   | 338 |
| Figure 2M-8  | Recreational and Cultural Interest Area Symbol Signs for Land Recreation.....                                    | 339 |
| Figure 2M-9  | Recreational and Cultural Interest Area Symbol Signs for Water Recreation .....                                  | 340 |
| Figure 2M-10 | Recreational and Cultural Interest Area Symbol Signs for Winter Recreation .....                                 | 341 |
| Figure 2N-1  | Emergency Management Signs .....   | 343 |
| Figure 3B-1  | Examples of Two-Lane, Two-Way Marking Applications .....   | 351 |
| Figure 3B-2  | Examples of Four-or-More Lane, Two-Way Marking Applications .....  | 352 |
| Figure 3B-3  | Examples of Three-Lane, Two-Way Marking Applications.....  | 353 |
| Figure 3B-4  | Method of Locating and Determining the Limits of No-Passing Zones at Curves .....                                | 354 |
| Figure 3B-5  | Example of Application of Three-Lane, Two-Way Marking for Changing Direction of the Center Lane .....            | 355 |
| Figure 3B-6  | Example of Reversible Lane Marking Application .....   | 357 |
| Figure 3B-7  | Example of Two-Way Left-Turn Lane Marking Applications .....   | 358 |
| Figure 3B-8  | Examples of Dotted Line and Channelizing Line Applications for Exit Ramp Markings....                            | 359 |
| Figure 3B-9  | Examples of Dotted Line and Channelizing Line Applications for Entrance Ramp Markings .....                      | 361 |
| Figure 3B-10 | Examples of Applications of Freeway and Expressway Lane-Drop Markings .....                                      | 364 |
| Figure 3B-11 | Examples of Applications of Conventional Road Lane-Drop Markings .....   | 369 |
| Figure 3B-12 | Example of Solid Double White Lines Used to Prohibit Lane Changing .....   | 371 |
| Figure 3B-13 | Examples of Line Extensions through Intersections .....  | 373 |
| Figure 3B-14 | Examples of Applications of Lane-Reduction Transition Markings .....   | 376 |
| Figure 3B-15 | Examples of Applications of Markings for Obstructions in the Roadway .....                                       | 378 |
| Figure 3B-16 | Recommended Yield Line Layouts .....   | 383 |
| Figure 3B-17 | Examples of Yield Lines at Unsignalized Midblock Crosswalks.....   | 384 |
| Figure 3B-18 | Do Not Block Intersection Markings .....   | 385 |
| Figure 3B-19 | Examples of Crosswalk Markings.....  | 385 |
| Figure 3B-20 | Example of Crosswalk Markings for an Exclusive Pedestrian Phase that Permits Diagonal Crossing .....             | 386 |
| Figure 3B-21 | Examples of Parking Space Markings .....   | 387 |
| Figure 3B-22 | International Symbol of Accessibility Parking Space Marking .....  | 388 |
| Figure 3B-23 | Example of Elongated Letters for Word Pavement Markings .....  | 388 |
| Figure 3B-24 | Examples of Standard Arrows for Pavement Markings .....  | 389 |
| Figure 3B-25 | Examples of Elongated Route Shields for Pavement Markings .....  | 391 |
| Figure 3B-26 | Yield Ahead Triangle Symbols .....   | 392 |
| Figure 3B-27 | Examples of Lane-Use Control Word and Arrow Pavement Markings .....  | 393 |
| Figure 3B-28 | Example of the Application of Speed Reduction Markings .....   | 395 |
| Figure 3B-29 | Pavement Markings for Speed Humps without Crosswalks.....  | 397 |
| Figure 3B-30 | Pavement Markings for Speed Tables or Speed Humps with Crosswalks .....  | 398 |
| Figure 3B-31 | Advance Warning Markings for Speed Humps .....   | 399 |
| Figure 3C-1  | Example of Markings for Approach and Circulatory Roadways at a Roundabout .....                                  | 400 |
| Figure 3C-2  | Lane-Use Arrow Pavement Marking Options for Roundabout Approaches .....  | 401 |
| Figure 3C-3  | Example of Markings for a One-Lane Roundabout .....  | 401 |
| Figure 3C-4  | Example of Markings for a Two-Lane Roundabout with One- and Two-Lane Approaches...                               | 402 |
| Figure 3C-5  | Example of Markings for a Two-Lane Roundabout with One-Lane Exits.....   | 404 |
| Figure 3C-6  | Example of Markings for a Two-Lane Roundabout with Two-Lane Exits.....   | 405 |
| Figure 3C-7  | Example of Markings for a Two-Lane Roundabout with a Double Left Turn .....                                      | 406 |
| Figure 3C-8  | Example of Markings for a Two-Lane Roundabout with a Double Right Turn .....                                     | 407 |
| Figure 3C-9  | Example of Markings for a Two-Lane Roundabout with Consecutive Double Lefts.....                                 | 408 |

|              |  |     |
|--------------|--|-----|
| Figure 3C-10 | Example of Markings for a Three-Lane Roundabout with Two- and Three-Lane Approaches.....   | 409 |
| Figure 3C-11 | Example of Markings for a Three-Lane Roundabout with Three-Lane Approaches .....   | 410 |
| Figure 3C-12 | Example of Markings for a Three-Lane Roundabout with Two-Lane Exits.....   | 411 |
| Figure 3C-13 | Example of Markings for Two Linked Roundabouts .....   | 412 |
| Figure 3C-14 | Example of Markings for a Diamond Interchange with Two Circular-Shaped Roundabout Ramp Terminals .....   | 413 |
| Figure 3D-1  | Markings for Barrier-Separated Preferential Lanes .....  | 419 |
| Figure 3D-2  | Markings for Buffer-Separated Preferential Lanes .....   | 419 |
| Figure 3D-3  | Markings for Contiguous Preferential Lanes .....   | 421 |
| Figure 3D-4  | Markings for Counter-Flow Preferential Lanes on Divided Highways .....   | 423 |
| Figure 3F-1  | Examples of Delineator Placement .....   | 426 |
| Figure 3J-1  | Examples of Longitudinal Rumble Strip Markings .....   | 433 |
| Figure 4C-1  | Warrant 2, Four-Hour Vehicular Volume .....  | 442 |
| Figure 4C-2  | Warrant 2, Four-Hour Vehicular Volume (70% Factor) .....   | 442 |
| Figure 4C-3  | Warrant 3, Peak Hour .....   | 443 |
| Figure 4C-4  | Warrant 3, Peak Hour (70% Factor) .....  | 443 |
| Figure 4C-5  | Warrant 4, Pedestrian Four-Hour Volume .....   | 445 |
| Figure 4C-6  | Warrant 4, Pedestrian Four-Hour Volume (70% Factor) .....  | 445 |
| Figure 4C-7  | Warrant 4, Pedestrian Peak Hour .....  | 446 |
| Figure 4C-8  | Warrant 4, Pedestrian Peak Hour (70% Factor) .....   | 446 |
| Figure 4C-9  | Warrant 9, Intersection Near a Grade Crossing (One Approach Lane at the Track Crossing) .....  | 449 |
| Figure 4C-10 | Warrant 9, Intersection Near a Grade Crossing (Two or More Approach Lanes at the Track Crossing) .....   | 449 |
| Figure 4D-1  | Example of U-Turn Signal Face .....  | 458 |
| Figure 4D-2  | Typical Arrangements of Signal Sections in Signal Faces That Do Not Control Turning Movements .....  | 460 |
| Figure 4D-3  | Recommended Vehicular Signal Faces for Approaches with Posted, Statutory, or 85 <sup>th</sup> Percentile Speed of 45 mph or Higher .....                     | 462 |
| Figure 4D-4  | Lateral and Longitudinal Location of Primary Signal Faces .....  | 465 |
| Figure 4D-5  | Maximum Mounting Height of Signal Faces Located Between 40 Feet and 53 Feet from Stop Line .....   | 467 |
| Figure 4D-6  | Typical Position and Arrangements of Shared Signal Faces for Permissive Only Mode Left Turns .....   | 469 |
| Figure 4D-7  | Typical Position and Arrangements of Separate Signal Faces with Flashing Yellow Arrow for Permissive Only Mode Left Turns .....                              | 470 |
| Figure 4D-8  | Typical Position and Arrangements of Separate Signal Faces with Flashing Red Arrow for Permissive Only Mode and Protected/Permissive Mode Left Turns .....   | 471 |
| Figure 4D-9  | Typical Positions and Arrangements of Shared Signal Faces for Protected Only Mode Left Turns .....   | 472 |
| Figure 4D-10 | Typical Position and Arrangements of Separate Signal Faces for Protected Only Mode Left Turns .....  | 473 |
| Figure 4D-11 | Typical Position and Arrangements of Shared Signal Faces for Protected/Permissive Mode Left Turns .....  | 474 |
| Figure 4D-12 | Typical Position and Arrangements of Separate Signal Faces with Flashing Yellow Arrow for Protected/Permissive Mode and Protected Only Mode Left Turns ..... | 475 |
| Figure 4D-13 | Typical Positions and Arrangements of Shared Signal Faces for Permissive Only Mode Right Turns .....   | 478 |
| Figure 4D-14 | Typical Position and Arrangements of Separate Signal Faces with Flashing Yellow Arrow for Permissive Only Mode Right Turns .....                             | 479 |
| Figure 4D-15 | Typical Position and Arrangements of Separate Signal Faces with Flashing Red Arrow for Permissive Only Mode and Protected/Permissive Mode Right Turns .....  | 480 |

|              |   |     |
|--------------|---|-----|
| Figure 4D-16 | Typical Positions and Arrangements of Shared Signal Faces for Protected Only Mode Right Turns .....   | 481 |
| Figure 4D-17 | Typical Position and Arrangements of Separate Signal Faces for Protected Only Mode Right Turns.....   | 482 |
| Figure 4D-18 | Typical Positions and Arrangements of Shared Signal Faces for Protected/Permissive Mode Right Turns .....   | 483 |
| Figure 4D-19 | Typical Position and Arrangements of Separate Signal Faces with Flashing Yellow Arrow for Protected/Permissive Mode and Protected Only Mode Right Turns ..... | 484 |
| Figure 4D-20 | Signal Indications for Approaches with a Shared Left-Turn/Right-Turn Lane and No Through Movement .....   | 488 |
| Figure 4E-1  | Typical Pedestrian Signal Indications .....   | 498 |
| Figure 4E-2  | Pedestrian Intervals .....  | 500 |
| Figure 4E-3  | Pushbutton Location Area.....   | 503 |
| Figure 4E-4  | Typical Pushbutton Locations .....  | 504 |
| Figure 4F-1  | Guidelines for the Installation of Pedestrian Hybrid Beacons on Low-Speed Roadways .....  | 512 |
| Figure 4F-2  | Guidelines for the Installation of Pedestrian Hybrid Beacons on High-Speed Roadways .....   | 512 |
| Figure 4F-3  | Sequence for a Pedestrian Hybrid Beacon .....   | 513 |
| Figure 4G-1  | Sequence for an Emergency-Vehicle Hybrid Beacon .....   | 517 |
| Figure 4M-1  | Left-Turn Lane-Use Control Signals .....  | 528 |
| Figure 5B-1  | Regulatory Signs on Low-Volume Roads .....  | 536 |
| Figure 5B-2  | Parking Signs and Plaques on Low-Volume Roads .....   | 537 |
| Figure 5C-1  | Horizontal Alignment and Intersection Warning Signs and Plaques and Object Markers on Low-Volume Roads .....  | 538 |
| Figure 5C-2  | Other Warning Signs and Plaques on Low-Volume Roads .....   | 540 |
| Figure 5F-1  | Highway-Rail Grade Crossing Signs and Plaques for Low-Volume Roads.....   | 544 |
| Figure 5G-1  | Temporary Traffic Control Signs and Plaques on Low-Volume Roads .....   | 547 |
| Figure 6C-1  | Component Parts of a Temporary Traffic Control Zone .....   | 555 |
| Figure 6C-2  | Types of Tapers and Buffer Spaces .....   | 558 |
| Figure 6C-3  | Example of a One-Lane, Two-Way Traffic Taper.....   | 561 |
| Figure 6E-1  | Example of the Use of a STOP/SLOW Automated Flagger Assistance Device (AFAD).....   | 572 |
| Figure 6E-2  | Example of the Use of a Red/Yellow Lens Automated Flagger Assistance Device (AFAD)..  | 574 |
| Figure 6E-3  | Use of Hand-Signaling Devices by Flaggers.....  | 576 |
| Figure 6F-1  | Height and Lateral Location of Signs—Typical Installations .....  | 583 |
| Figure 6F-2  | Methods of Mounting Signs Other Than on Posts .....   | 584 |
| Figure 6F-3  | Regulatory Signs and Plaques in Temporary Traffic Control Zones.....  | 586 |
| Figure 6F-4  | Warning Signs and Plaques in Temporary Traffic Control Zones.....   | 590 |
| Figure 6F-5  | Exit Open and Closed and Detour Signs .....   | 594 |
| Figure 6F-6  | Advance Warning Arrow Board Display Specifications .....  | 604 |
| Figure 6F-7  | Channelizing Devices .....  | 607 |
| Figure 6H-1  | Work Beyond the Shoulder (TA-1) .....   | 637 |
| Figure 6H-2  | Blasting Zone (TA-2) .....  | 639 |
| Figure 6H-3  | Work on the Shoulders (TA-3) .....  | 641 |
| Figure 6H-4  | Short-Duration or Mobile Operation on a Shoulder (TA-4) .....   | 643 |
| Figure 6H-5  | Shoulder Closure on a Freeway (TA-5) .....  | 645 |
| Figure 6H-6  | Shoulder Work with Minor Encroachment (TA-6) .....  | 647 |
| Figure 6H-7  | Road Closure with a Diversion (TA-7) .....  | 649 |
| Figure 6H-8  | Road Closure with an Off-Site Detour (TA-8) .....   | 651 |
| Figure 6H-9  | Overlapping Routes with a Detour (TA-9) .....   | 653 |
| Figure 6H-10 | Lane Closure on a Two-Lane Road Using Flaggers (TA-10) .....  | 655 |
| Figure 6H-11 | Lane Closure on a Two-Lane Road with Low Traffic Volumes (TA-11).....   | 657 |
| Figure 6H-12 | Lane Closure on a Two-Lane Road Using Traffic Control Signals (TA-12).....  | 659 |
| Figure 6H-13 | Temporary Road Closure (TA-13) .....  | 661 |
| Figure 6H-14 | Haul Road Crossing (TA-14) .....  | 663 |
| Figure 6H-15 | Work in the Center of a Road with Low Traffic Volumes (TA-15) .....   | 665 |

|              |  |     |
|--------------|--|-----|
| Figure 6H-16 | Surveying Along the Center Line of a Road with Low Traffic Volumes (TA-16).....                  | 667 |
| Figure 6H-17 | Mobile Operations on a Two-Lane Road (TA-17).....  | 669 |
| Figure 6H-18 | Lane Closure on a Minor Street (TA-18).....  | 671 |
| Figure 6H-19 | Detour for One Travel Direction (TA-19).....   | 673 |
| Figure 6H-20 | Detour for a Closed Street (TA-20) .....   | 675 |
| Figure 6H-21 | Lane Closure on the Near Side of an Intersection (TA-21) .....                                   | 677 |
| Figure 6H-22 | Right-Hand Lane Closure on the Far Side of an Intersection (TA-22).....                          | 679 |
| Figure 6H-23 | Left-Hand Lane Closure on the Far Side of an Intersection (TA-23).....                           | 681 |
| Figure 6H-24 | Half Road Closure on the Far Side of an Intersection (TA-24) .....                               | 683 |
| Figure 6H-25 | Multiple Lane Closures at an Intersection (TA-25).....   | 685 |
| Figure 6H-26 | Closure in the Center of an Intersection (TA-26).....  | 687 |
| Figure 6H-27 | Closure at the Side of an Intersection (TA-27).....  | 689 |
| Figure 6H-28 | Sidewalk Detour or Diversion (TA-28) .....   | 691 |
| Figure 6H-29 | Crosswalk Closures and Pedestrian Detours (TA-29) .....  | 693 |
| Figure 6H-30 | Interior Lane Closure on a Multi-Lane Street (TA-30) .....                                       | 695 |
| Figure 6H-31 | Lane Closures on a Street with Uneven Directional Volumes (TA-31) .....                          | 697 |
| Figure 6H-32 | Half Road Closure on a Multi-Lane, High-Speed Highway (TA-32) .....                              | 699 |
| Figure 6H-33 | Stationary Lane Closure on a Divided Highway (TA-33) .....                                       | 701 |
| Figure 6H-34 | Lane Closure with a Temporary Traffic Barrier (TA-34) .....                                      | 703 |
| Figure 6H-35 | Mobile Operation on a Multi-Lane Road (TA-35) .....  | 705 |
| Figure 6H-36 | Lane Shift on a Freeway (TA-36).....   | 707 |
| Figure 6H-37 | Double Lane Closure on a Freeway (TA-37).....  | 709 |
| Figure 6H-38 | Interior Lane Closure on a Freeway (TA-38) .....   | 711 |
| Figure 6H-39 | Median Crossover on a Freeway (TA-39) .....  | 713 |
| Figure 6H-40 | Median Crossover for an Entrance Ramp (TA-40) .....  | 715 |
| Figure 6H-41 | Median Crossover for an Exit Ramp (TA-41) .....  | 717 |
| Figure 6H-42 | Work in the Vicinity of an Exit Ramp (TA-42) .....   | 719 |
| Figure 6H-43 | Partial Exit Ramp Closure (TA-43) .....  | 721 |
| Figure 6H-44 | Work in the Vicinity of an Entrance Ramp (TA-44).....  | 723 |
| Figure 6H-45 | Temporary Reversible Lane Using Movable Barriers (TA-45) .....                                   | 725 |
| Figure 6H-46 | Work in the Vicinity of a Grade Crossing (TA-46).....  | 727 |
| Figure 6I-1  | Examples of Traffic Incident Management Area Signs .....   | 729 |
| Figure 7A-1  | Example of School Route Plan Map.....  | 734 |
| Figure 7B-1  | School Area Signs .....  | 737 |
| Figure 7B-2  | Example of Signing for a Higher Fines School Zone without a School Crossing .....                | 739 |
| Figure 7B-3  | Example of Signing for a Higher Fines School Zone with a School Speed Limit .....                | 740 |
| Figure 7B-4  | Example of Signing for a School Crossing Outside of a School Zone .....                          | 741 |
| Figure 7B-5  | Example of Signing for a School Zone with a School Speed Limit and a School Crossing ..          | 742 |
| Figure 7B-6  | In-Street Signs in School Areas .....  | 743 |
| Figure 7C-1  | Two-Lane Pavement Marking of "SCHOOL" .....  | 746 |
| Figure 8B-1  | Regulatory Signs and Plaques for Grade Crossings .....   | 755 |
| Figure 8B-2  | Crossbuck Assembly with a YIELD or STOP Sign on the Crossbuck Sign Support .....                 | 756 |
| Figure 8B-3  | Crossbuck Assembly with a YIELD or STOP Sign on a Separate Sign Support .....                    | 757 |
| Figure 8B-4  | Warning Signs and Plaques for Grade Crossings .....  | 761 |
| Figure 8B-5  | Example of an Emergency Notification Sign .....  | 763 |
| Figure 8B-6  | Example of Placement of Warning Signs and Pavement Markings at Grade Crossings .....             | 767 |
| Figure 8B-7  | Grade Crossing Pavement Markings .....   | 768 |
| Figure 8B-8  | Example of Dynamic Envelope Pavement Markings at Grade Crossings .....                           | 769 |
| Figure 8B-9  | Examples of Light Rail Transit Vehicle Dynamic Envelope Markings for Mixed-Use Alignments .....  | 770 |
| Figure 8C-1  | Composite Drawing of Active Traffic Control Devices for Grade Crossings Showing Clearances ..... | 772 |
| Figure 8C-2  | Example of Location Plan for Flashing-Light Signals and Four-Quadrant Gates.....                 | 776 |
| Figure 8C-3  | Light Rail Transit Signals.....  | 781 |

|              |   |     |
|--------------|---|-----|
| Figure 8C-4  | Example of Flashing-Light Signal Assembly for Pedestrian Crossings .....  | 783 |
| Figure 8C-5  | Example of a Shared Pedestrian/Roadway Gate .....   | 784 |
| Figure 8C-6  | Example of a Separate Pedestrian Gate .....   | 784 |
| Figure 8C-7  | Examples of Placement of Pedestrian Gates .....   | 785 |
| Figure 8C-8  | Example of Swing Gates .....  | 786 |
| Figure 8C-9  | Example of Pedestrian Barriers at an Offset Grade Crossing .....  | 786 |
| Figure 8C-10 | Examples of Pedestrian Barrier Installation at an Offset Non-Intersection Grade Crossing...   | 787 |
| Figure 8D-1  | Example of Signing and Markings for a Pathway Grade Crossing .....  | 789 |
| Figure 9B-1  | Sign Placement on Shared-Use Paths .....  | 792 |
| Figure 9B-2  | Regulatory Signs and Plaques for Bicycle Facilities .....   | 795 |
| Figure 9B-3  | Warning Signs and Plaques and Object Markers for Bicycle Facilities .....   | 799 |
| Figure 9B-4  | Guide Signs and Plaques for Bicycle Facilities .....  | 801 |
| Figure 9B-5  | Example of Signing for the Beginning and End of a Designated Bicycle Route on a Shared-Use Path .....   | 803 |
| Figure 9B-6  | Example of Bicycle Guide Signing .....  | 804 |
| Figure 9B-7  | Examples of Signing and Markings for a Shared-Use Path Crossing .....   | 805 |
| Figure 9B-8  | Example of Mode-Specific Guide Signing on a Shared-Use Path .....   | 807 |
| Figure 9C-1  | Example of Intersection Pavement Markings—Designated Bicycle Lane with Left-Turn Area, Heavy Turn Volumes, Parking, One-Way Traffic, or Divided Highway ..... | 809 |
| Figure 9C-2  | Examples of Center Line Markings for Shared-Use Paths .....   | 810 |
| Figure 9C-3  | Word, Symbol, and Arrow Pavement Markings for Bicycle Lanes .....   | 811 |
| Figure 9C-4  | Example of Bicycle Lane Treatment at a Right Turn Only Lane .....   | 813 |
| Figure 9C-5  | Example of Bicycle Lane Treatment at Parking Lane into a Right Turn Only Lane .....   | 814 |
| Figure 9C-6  | Example of Pavement Markings for Bicycle Lanes on a Two-Way Street.....   | 815 |
| Figure 9C-7  | Bicycle Detector Pavement Marking .....   | 816 |
| Figure 9C-8  | Examples of Obstruction Pavement Markings .....   | 817 |
| Figure 9C-9  | Shared Lane Marking .....   | 817 |

## TABLES

### Page

|            |   |     |
|------------|---|-----|
| Table I-1  | Evolution of the MUTCD.....   | I-2 |
| Table I-2  | Target Compliance Dates Established by the FHWA .....                           | I-4 |
| Table 1A-1 | Acceptable Abbreviations .....  | 24  |
| Table 1A-2 | Abbreviations that Shall be Used Only on Portable Changeable Message Signs..... | 25  |
| Table 1A-3 | Unacceptable Abbreviations.....   | 26  |
| Table 2A-1 | Illumination of Sign Elements.....  | 29  |
| Table 2A-2 | Retroreflection of Sign Elements.....   | 29  |
| Table 2A-3 | Minimum Maintained Retroreflectivity Levels.....                                | 31  |
| Table 2A-4 | Use of Sign Shapes .....  | 32  |
| Table 2A-5 | Common Uses of Sign Colors .....  | 33  |
| Table 2B-1 | Regulatory Sign and Plaque Sizes.....   | 46  |
| Table 2B-2 | Meanings of Symbols and Legends on Reversible Lane Control Signs .....          | 65  |
| Table 2C-1 | Categories of Warning Signs and Plaques.....                                    | 104 |
| Table 2C-2 | Warning Sign and Plaque Sizes.....  | 105 |
| Table 2C-3 | Minimum Size of Supplemental Warning Plaques .....                              | 107 |
| Table 2C-4 | Guidelines for Advance Placement of Warning Signs .....                         | 108 |
| Table 2C-5 | Horizontal Alignment Sign Selection .....                                       | 110 |
| Table 2C-6 | Approximate Spacing of Chevron Alignment Signs on Horizontal Curves.....        | 113 |
| Table 2D-1 | Conventional Road Guide Sign Sizes .....  | 139 |
| Table 2D-2 | Recommended Minimum Letter Heights on Street Name Signs .....                   | 163 |
| Table 2E-1 | Freeway or Expressway Guide Sign and Plaque Sizes .....                         | 186 |

|            |  |      |
|------------|--|------|
| Table 2E-2 | Minimum Letter and Numeral Sizes for Expressway Guide Signs According to Interchange Classification .....  | 188  |
| Table 2E-3 | Minimum Letter and Numeral Sizes for Expressway Guide Signs According to Sign Type..   | 189  |
| Table 2E-4 | Minimum Letter and Numeral Sizes for Freeway Guide Signs According to Interchange Classification .....   | 190  |
| Table 2E-5 | Minimum Letter and Numeral Sizes for Freeway Guide Signs According to Sign Type ..   | 191  |
| Table 2F-1 | Toll Facility Sign and Plaque Minimum Sizes .....  | 237  |
| Table 2G-1 | Managed and Preferential Lanes Sign and Plaque Minimum Sizes.....  | 254  |
| Table 2H-1 | General Information Sign Sizes .....   | 292  |
| Table 2I-1 | General Service Sign and Plaque Sizes .....  | 299  |
| Table 2J-1 | Minimum Letter and Numeral Sizes for Specific Service Signs According to Sign Type.....  | 316  |
| Table 2L-1 | Example of Units of Information .....  | 328  |
| Table 2M-1 | Category Chart for Recreational and Cultural Interest Area Symbols.....  | 331  |
| Table 2N-1 | Emergency Management Sign Sizes .....  | 343  |
| Table 3B-1 | Minimum Passing Sight Distances for No-Passing Zone Markings .....   | 353  |
| Table 3D-1 | Standard Edge Line and Lane Line Markings for Preferential Lanes.....  | 418  |
| Table 3F-1 | Approximate Spacing for Delineators on Horizontal Curves .....   | 428  |
| Table 4C-1 | Warrant 1, Eight-Hour Vehicular Volume .....   | 440  |
| Table 4C-2 | Warrant 9, Adjustment Factor for Daily Frequency of Rail Traffic.....  | 450  |
| Table 4C-3 | Warrant 9, Adjustment Factor for Percentage of High-Occupancy Buses.....   | 450  |
| Table 4C-4 | Warrant 9, Adjustment Factor for Percentage of Tractor-Trailer Trucks .....  | 450  |
| Table 4D-1 | Recommended Minimum Number of Primary Signal Faces for Through Traffic on Approaches with Posted, Statutory, or 85 <sup>th</sup> -Percentile Speed of 45 mph or Higher ..... | 463  |
| Table 4D-2 | Minimum Sight Distance for Signal Visibility .....   | 463  |
| Table 5A-1 | Sign and Plaque Sizes on Low-Volume Roads .....  | 534  |
| Table 6C-1 | Recommended Advance Warning Sign Minimum Spacing.....  | 556  |
| Table 6C-2 | Stopping Sight Distance as a Function of Speed.....  | 557  |
| Table 6C-3 | Taper Length Criteria for Temporary Traffic Control Zones .....  | 559  |
| Table 6C-4 | Formulas for Determining Taper Length .....  | 559  |
| Table 6E-1 | Stopping Sight Distance as a Function of Speed.....  | 577  |
| Table 6F-1 | Temporary Traffic Control Zone Sign and Plaque Sizes .....   | 580  |
| Table 6H-1 | Index to Typical Applications .....  | 634  |
| Table 6H-2 | Meaning of Symbols on Typical Application Diagrams .....   | 635  |
| Table 6H-3 | Meaning of Letter Codes on Typical Application Diagrams .....  | 635  |
| Table 6H-4 | Formulas for Determining Taper Length .....  | 635  |
| Table 7B-1 | School Area Sign and Plaque Sizes.....   | 735  |
| Table 8B-1 | Grade Crossing Sign and Plaque Minimum Sizes .....   | 754  |
| Table 9B-1 | Bicycle Facility Sign and Plaque Minimum Sizes .....   | 793  |
| Table A2-1 | Conversion of Inches to Millimeters .....  | A2-1 |
| Table A2-2 | Conversion of Feet to Meters .....   | A2-1 |
| Table A2-3 | Conversion of Miles to Kilometers .....  | A2-1 |
| Table A2-4 | Conversion of Miles per Hour to Kilometers/Hour .....  | A2-1 |

**Table I-2. Target Compliance Dates Established by the FHWA**

| <b>2009 MUTCD Section Number(s)</b> | <b>2009 MUTCD Section Title</b> | <b>Specific Provision</b>  | <b>Compliance Date</b>   |
|-------------------------------------|---------------------------------|--|--|
| Rev. 2                              | 2A.08                           | Maintaining Minimum Retroreflectivity                                    | Implementation and continued use of an assessment or management method that is designed to maintain regulatory and warning sign retroreflectivity at or above the established minimum levels (see Paragraph 2)<br>June 13, 2014*   |
|                                     | 2A.19                           | Lateral Offset   | Crashworthiness of sign supports on roads with posted speed limit of 50 mph or higher (see Paragraph 2)<br>January 17, 2013 (date established in the 2000 MUTCD)   |
|                                     | 2B.40                           | ONE WAY Signs (R6-1, R6-2)   | New requirements in the 2009 MUTCD for the number and locations of ONE WAY signs (see Paragraphs 4, 9, and 10)<br>December 31, 2019  |
| Rev. 3                              | 2C.06 through 2C.14             | Horizontal Alignment Warning Signs                                       | Revised requirements in the 2009 MUTCD regarding the use of various horizontal alignment signs (see Table 2C-5)<br>December 31, 2019   |
|                                     | 2E.31, 2E.33, and 2E.36         | Plaques for Left-Hand Exits  | New requirement in the 2009 MUTCD to use E1-5aP and E1-5bP plaques for left-hand exits<br>December 31, 2014  |
|                                     | 3A.03                           | Maintaining Minimum Retroreflectivity                                    | Implementation and continued use of a method that is designed to maintain retroreflectivity of longitudinal pavement markings (see Paragraph 1)<br>4 years from the effective date of this revision of the MUTCD   |
| Rev. 2                              | 4D.26                           | Yellow Change and Red Clearance Intervals                                | New requirement in the 2009 MUTCD that durations of yellow change and red clearance intervals shall be determined using engineering practices (see Paragraphs 3 and 6)<br>June 13, 2014, or when timing adjustments are made to the individual intersection and/or corridor, whichever occurs first                                    |
|                                     | 4E.06                           | Pedestrian Intervals and Signal Phases                                   | New requirement in the 2009 MUTCD that the pedestrian change interval shall not extend into the red clearance interval and shall be followed by a buffer interval of at least 3 seconds (see Paragraph 4)<br>June 13, 2014, or when timing adjustments are made to the individual intersection and/or corridor, whichever occurs first |
|                                     | 6D.03**                         | Worker Safety Considerations   | New requirement in the 2009 MUTCD that all workers within the right-of-way shall wear high-visibility apparel (see Paragraphs 4, 6, and 7)<br>December 31, 2011  |
| Rev. 2                              | 6E.02**                         | High-Visibility Safety Apparel   | New requirement in the 2009 MUTCD that all flaggers within the right-of-way shall wear high-visibility apparel<br>December 31, 2011  |
|                                     | 7D.04**                         | Uniform of Adult Crossing Guards   | New requirement in the 2009 MUTCD for high-visibility apparel for adult crossing guards<br>December 31, 2011   |
|                                     | 8B.03, 8B.04                    | Grade Crossing (Crossbuck) Signs and Supports                            | Retroreflective strip on Crossbuck sign and support (see Paragraph 7 in Section 8B.03 and Paragraphs 15 and 18 in Section 8B.04)<br>December 31, 2019  |
|                                     | 8B.04                           | Crossbuck Assemblies with YIELD or STOP Signs at Passive Grade Crossings | New requirement in the 2009 MUTCD for the use of STOP or YIELD signs with Crossbuck signs at passive grade crossings<br>December 31, 2019  |

\* Types of signs other than regulatory or warning are to be added to an agency's management or assessment method as resources allow.

\*\* MUTCD requirement is a result of a legislative mandate.

Note: All compliance dates that were previously published in Table I-2 of the 2009 MUTCD and that do not appear in this revised table have been eliminated.

04 Other publications that are useful sources of information with respect to the use of this Manual are listed in this paragraph. See Page i of this Manual for ordering information for the following publications (later editions might also be available as useful sources of information):

1. "AAA School Safety Patrol Operations Manual," 2006 Edition (American Automobile Association—AAA)
2. "A Policy on Geometric Design of Highways and Streets," 2004 Edition (American Association of State Highway and Transportation Officials—AASHTO)
3. "Guide for the Development of Bicycle Facilities," 1999 Edition (AASHTO)
4. "Guide for the Planning, Design, and Operation of Pedestrian Facilities," 2004 Edition (AASHTO)
5. "Guide to Metric Conversion," 1993 Edition (AASHTO)
6. "Guidelines for the Selection of Supplemental Guide Signs for Traffic Generators Adjacent to Freeways," 4th Edition/Guide Signs, Part II: Guidelines for Airport Guide Signing/Guide Signs, Part III: List of Control Cities for Use in Guide Signs on Interstate Highways," Item Code: GSGLC-4, 2001 Edition (AASHTO)
7. "Roadside Design Guide," 2006 Edition (AASHTO)
8. "Standard Specifications for Movable Highway Bridges," 1988 Edition (AASHTO)
9. "Traffic Engineering Metric Conversion Folders—Addendum to the Guide to Metric Conversion," 1993 Edition (AASHTO)
10. "2009 AREMA Communications & Signals Manual," (American Railway Engineering & Maintenance-of-Way Association—AREMA)
11. "Changeable Message Sign Operation and Messaging Handbook (FHWA-OP-03-070)," 2004 Edition (Federal Highway Administration—FHWA)
12. "Designing Sidewalks and Trails for Access—Part 2—Best Practices Design Guide (FHWA-EP-01-027)," 2001 Edition (FHWA)
13. "Federal-Aid Highway Program Guidance on High Occupancy Vehicle (HOV) Lanes," 2001 (FHWA)
14. "Maintaining Traffic Sign Retroreflectivity," 2007 Edition (FHWA)
15. "Railroad-Highway Grade Crossing Handbook—Revised Second Edition (FHWA-SA-07-010)," 2007 Edition (FHWA)
16. "Ramp Management and Control Handbook (FHWA-HOP-06-001)," 2006 Edition (FHWA)
17. "Roundabouts—An Informational Guide (FHWA-RD-00-067)," 2000 Edition (FHWA)
18. "Signal Timing Manual (FHWA-HOP-08-024)," 2008 Edition (FHWA)
19. "Signalized Intersections: an Informational Guide (FHWA-HRT-04-091)," 2004 Edition (FHWA)
20. "Travel Better, Travel Longer: A Pocket Guide to Improving Traffic Control and Mobility for Our Older Population (FHWA-OP-03-098)," 2003 Edition (FHWA)
21. "Practice for Roadway Lighting," RP-8, 2001 (Illuminating Engineering Society—IES)
22. "Safety Guide for the Prevention of Radio Frequency Radiation Hazards in the Use of Commercial Electric Detonators (Blasting Caps)," Safety Library Publication No. 20, July 2001 Edition (Institute of Makers of Explosives)
23. "American National Standard for High-Visibility Public Safety Vests," (ANSI/ISEA 207-2006), 2006 Edition (International Safety Equipment Association—ISEA)
24. "American National Standard for High-Visibility Safety Apparel and Headwear," (ANSI/ISEA 107-2004), 2004 Edition (ISEA)
25. "Manual of Traffic Signal Design," 1998 Edition (Institute of Transportation Engineers—ITE)
26. "Manual of Transportation Engineering Studies," 1994 Edition (ITE)
27. "Pedestrian Traffic Control Signal Indications," Part 1—1985 Edition; Part 2 (LED Pedestrian Traffic Signal Modules)—2004 Edition (ITE)
28. "Preemption of Traffic Signals Near Railroad Crossings," 2006 Edition (ITE)
29. "Purchase Specification for Flashing and Steady Burn Warning Lights," 1981 Edition (ITE)
30. "Traffic Control Devices Handbook," 2001 Edition (ITE)
31. "Traffic Detector Handbook," 1991 Edition (ITE)
32. "Traffic Engineering Handbook," 2009 Edition (ITE)
33. "Traffic Signal Lamps," 1980 Edition (ITE)
34. "Vehicle Traffic Control Signal Heads," Part 1—1985 Edition; Part 2 (LED Circular Signal Supplement)—2005 Edition; Part 3 (LED Vehicular Arrow Traffic Signal Supplement)—2004 Edition (ITE)
35. "Uniform Vehicle Code (UVC) and Model Traffic Ordinance," 2000 Edition (National Committee on Uniform Traffic Laws and Ordinances—NCUTLO)
36. "NEMA Standards Publication TS 4-2005 Hardware Standards for Dynamic Message Signs (DMS) With NTCIP Requirements," 2005 Edition (National Electrical Manufacturers Association—NEMA)
37. "Occupational Safety and Health Administration Regulations (Standards - 29 CFR), General Safety and Health Provisions - 1926.20," amended June 30, 1993 (Occupational Safety and Health Administration—OSHA)
38. "Accessible Pedestrian Signals—A Guide to Best Practices (NCHRP Web-Only Document 117A)," 2008 Edition (Transportation Research Board—TRB)
39. "Guidelines for Accessible Pedestrian Signals (NCHRP Web-Only Document 117B)," 2008 Edition (TRB)

- Rev. 3 |
40. "Highway Capacity Manual," 2000 Edition (TRB)
  41. "Recommended Procedures for the Safety Performance Evaluation of Highway Features," (NCHRP Report 350), 1993 Edition (TRB)
  42. "The Americans with Disabilities Act Accessibility Guidelines for Buildings and Facilities (ADAAG)," July 1998 Edition (The U.S. Access Board)
  43. "Methods for Maintaining Pavement Marking Retroreflectivity," (FHWA-SA-22-028), 2022 Edition (FHWA)

## **Section 1A.12 Color Code**

### **Support:**

- 01 The following color code establishes general meanings for 11 colors of a total of 13 colors that have been identified as being appropriate for use in conveying traffic control information. tolerance limits for each color are contained in 23 CFR Part 655, Appendix to Subpart F and are available at the Federal Highway Administration's MUTCD website at <http://mutcd.fhwa.dot.gov> or by writing to the FHWA, Office of Safety Research and Development (HRD-T-301), 6300 Georgetown Pike, McLean, VA 22101.
- 02 The two colors for which general meanings have not yet been assigned are being reserved for future applications that will be determined only by FHWA after consultation with the States, the engineering community, and the general public. The meanings described in this Section are of a general nature. More specific assignments of colors are given in the individual Parts of this Manual relating to each class of devices.

### **Standard:**

- 03 **The general meaning of the 13 colors shall be as follows:**
  - A. Black—regulation
  - B. Blue—road user services guidance, tourist information, and evacuation route
  - C. Brown—recreational and cultural interest area guidance
  - D. Coral—unassigned
  - E. Fluorescent Pink—incident management
  - F. Fluorescent Yellow-Green—pedestrian warning, bicycle warning, playground warning, school bus and school warning
  - G. Green—indicated movements permitted, direction guidance
  - H. Light Blue—unassigned
  - I. Orange—temporary traffic control
  - J. Purple—lanes restricted to use only by vehicles with registered electronic toll collection (ETC) accounts
  - K. Red—stop or prohibition
  - L. White—regulation
  - M. Yellow—warning

## **Section 1A.13 Definitions of Headings, Words, and Phrases in this Manual**

### **Standard:**

- 01 When used in this Manual, the text headings of Standard, Guidance, Option, and Support shall be defined as follows:
  - A. Standard—a statement of required, mandatory, or specifically prohibitive practice regarding a traffic control device. All Standard statements are labeled, and the text appears in bold type. The verb "shall" is typically used. The verbs "should" and "may" are not used in Standard statements. Standard statements are sometimes modified by Options.
  - B. Guidance—a statement of recommended, but not mandatory, practice in typical situations, with deviations allowed if engineering judgment or engineering study indicates the deviation to be appropriate. All Guidance statements are labeled, and the text appears in unbold type. The verb "should" is typically used. The verbs "shall" and "may" are not used in Guidance statements. Guidance statements are sometimes modified by Options.
  - C. Option—a statement of practice that is a permissive condition and carries no requirement or recommendation. Option statements sometime contain allowable modifications to a Standard or Guidance statement. All Option statements are labeled, and the text appears in unbold type. The verb "may" is typically used. The verbs "shall" and "should" are not used in Option statements.
  - D. Support—an informational statement that does not convey any degree of mandate, recommendation, authorization, prohibition, or enforceable condition. Support statements are labeled, and the text appears in unbold type. The verbs "shall," "should," and "may" are not used in Support statements.

## PART 3

### MARKINGS

#### CHAPTER 3A. GENERAL

##### **Section 3A.01 Functions and Limitations**

Support:

- 01 Markings on highways and on private roads open to public travel have important functions in providing guidance and information for the road user. Major marking types include pavement and curb markings, delineators, colored pavements, channelizing devices, and islands. In some cases, markings are used to supplement other traffic control devices such as signs, signals, and other markings. In other instances, markings are used alone to effectively convey regulations, guidance, or warnings in ways not obtainable by the use of other devices.
- 02 Markings have limitations. Visibility of the markings can be limited by snow, debris, and water on or adjacent to the markings. Marking durability is affected by material characteristics, traffic volumes, weather, and location. However, under most highway conditions, markings provide important information while allowing minimal diversion of attention from the roadway.

##### **Section 3A.02 Standardization of Application**

Standard:

- 01 Each standard marking shall be used only to convey the meaning prescribed for that marking in this Manual. When used for applications not described in this Manual, markings shall conform in all respects to the principles and standards set forth in this Manual.

Guidance:

- 02 Before any new highway, private road open to public travel (see definition in Section 1A.13), paved detour, or temporary route is opened to public travel, all necessary markings should be in place.

Standard:

- 03 Markings that must be visible at night shall be retroreflective unless ambient illumination assures that the markings are adequately visible. All markings on Interstate highways shall be retroreflective.
- 04 Markings that are no longer applicable for roadway conditions or restrictions and that might cause confusion for the road user shall be removed or obliterated to be unidentifiable as a marking as soon as practical.

Option:

- 05 Until they can be removed or obliterated, markings may be temporarily masked with tape that is approximately the same color as the pavement.

##### **Section 3A.03 Maintaining Minimum Pavement Marking Retroreflectivity**

Standard:

- 01 Except as provided in Paragraph 5, a method designed to maintain retroreflectivity at or above 50 mcd/m<sup>2</sup>/lx under dry conditions shall be used for longitudinal markings on roadways with speed limits of 35 mph or greater.

Guidance:

- 02 Except as provided in Paragraph 5, a method designed to maintain retroreflectivity at or above 100 mcd/m<sup>2</sup>/lx under dry conditions should be used for longitudinal markings on roadways with speed limits of 70 mph or greater.

- 03 The method used to maintain retroreflectivity should be one or more of those described in "Methods for Maintaining Pavement Marking Retroreflectivity" (see Section 1A.11) or developed from an engineering study based on the values in Paragraphs 1 and 2.

Support:

- 04 Retroreflectivity levels for pavement markings are measured with an entrance angle of 88.76 degrees and an observation angle of 1.05 degrees. This geometry is also referred to as 30-meter geometry. The units of pavement marking retroreflectivity are reported in mcd/m<sup>2</sup>/lx, which means millicandela per square meter per lux.

Option:

- 05 The following markings may be excluded from the provisions established in Paragraphs 1 and 2:
  - A. Markings where ambient illumination assures that the markings are adequately visible;
  - B. Markings on streets or highways that have an ADT of less than 6,000 vehicles per day;

- Rev. 3
- C. Dotted extension lines that extend a longitudinal line through an intersection, major driveway, or interchange area (see Section 3B.08);
  - D. Curb markings;
  - E. Parking space markings; and
  - F. Shared-use path markings.

**Support:**

- 06 The provisions of this Section do not apply to non-longitudinal pavement markings including, but not limited to, the following:
  - A. Transverse markings;
  - B. Word, symbol, and arrow markings;
  - C. Crosswalk markings; and
  - D. Chevron, diagonal, and crosshatch markings.

- 07 Special circumstances will periodically cause pavement marking retroreflectivity to be below the minimum levels. These circumstances include, but are not limited to, the following:
  - A. Isolated locations of abnormal degradation;
  - B. Periods preceding imminent resurfacing or reconstruction;
  - C. Unanticipated events such as equipment breakdowns, material shortages, and contracting problems; and
  - D. Loss of retroreflectivity resulting from snow maintenance operations.

When such circumstances occur, compliance with Paragraphs 1 and 2 is still considered to be achieved if a reasonable course of action is taken to resume maintenance of minimum retroreflectivity in a timely manner according to the maintaining agency's method(s), policies, and procedures.

## **Section 3A.04 Materials**

**Support:**

- 01 Pavement and curb markings are commonly placed by using paints or thermoplastics; however, other suitable marking materials, including raised pavement markers and colored pavements, are also used. Delineators and channelizing devices are visibly placed in a vertical position similar to signs above the roadway.
- 02 Some marking systems consist of clumps or droplets of material with visible open spaces of bare pavement between the material droplets. These marking systems can function in a manner that is similar to the marking systems that completely cover the pavement surface and are suitable for use as pavement markings if they meet the other pavement marking requirements of the highway agency.

**Guidance:**

- 03 *The materials used for markings should provide the specified color throughout their useful life.*
- 04 *Consideration should be given to selecting pavement marking materials that will minimize tripping or loss of traction for road users, including pedestrians, bicyclists, and motorcyclists.*
- 05 *Delineators should not present a vertical or horizontal clearance obstacle for pedestrians.*

## **Section 3A.05 Colors**

**Standard:**

- 01 **Markings shall be yellow, white, red, blue, or purple. The colors for markings shall conform to the standard highway colors. Black in conjunction with one of the colors mentioned in the first sentence of this paragraph shall be a usable color.**
- 02 **When used, white markings for longitudinal lines shall delineate:**
  - A. The separation of traffic flows in the same direction, or
  - B. The right-hand edge of the roadway.
- 03 **When used, yellow markings for longitudinal lines shall delineate:**
  - A. The separation of traffic traveling in opposite directions,
  - B. The left-hand edge of the roadways of divided highways and one-way streets or ramps, or
  - C. The separation of two-way left-turn lanes and reversible lanes from other lanes.
- 04 **When used, red raised pavement markers or delineators shall delineate:**
  - A. Truck escape ramps, or
  - B. One-way roadways, ramps, or travel lanes that shall not be entered or used in the direction from which the markers are visible.

05 When used, blue markings shall supplement white markings for parking spaces for persons with disabilities.

06 When used, purple markings shall supplement lane line or edge line markings for toll plaza approach lanes that are restricted to use only by vehicles with registered electronic toll collection accounts.

Option:

07 Colors used for official route shield signs (see Section 2D.11) may be used as colors of symbol markings to simulate route shields on the pavement (see Section 3B.20.)

08 Black may be used in combination with the colors mentioned in the first sentence of Paragraph 1 where a light-colored pavement does not provide sufficient contrast with the markings.

Support:

09 When used in combination with other colors, black is not considered a marking color, but only a contrast-enhancing system for the markings.

## **Section 3A.06 Functions, Widths, and Patterns of Longitudinal Pavement Markings**

Standard:

01 The general functions of longitudinal lines shall be:

- A. A double line indicates maximum or special restrictions,
- B. A solid line discourages or prohibits crossing (depending on the specific application),
- C. A broken line indicates a permissive condition, and
- D. A dotted line provides guidance or warning of a downstream change in lane function.

02 The widths and patterns of longitudinal lines shall be as follows:

- A. Normal line—4 to 6 inches wide.
- B. Wide line—at least twice the width of a normal line.
- C. Double line—two parallel lines separated by a discernible space.
- D. Broken line—normal line segments separated by gaps.
- E. Dotted line—noticeably shorter line segments separated by shorter gaps than used for a broken line. The width of a dotted line extension shall be at least the same as the width of the line it extends.

Support:

03 The width of the line indicates the degree of emphasis.

Guidance:

04 *Broken lines should consist of 10-foot line segments and 30-foot gaps, or dimensions in a similar ratio of line segments to gaps as appropriate for traffic speeds and need for delineation.*

Support:

05 Patterns for dotted lines depend on the application (see Sections 3B.04 and 3B.08.)

Guidance:

06 *A dotted line for line extensions within an intersection or taper area should consist of 2-foot line segments and 2- to 6-foot gaps. A dotted line used as a lane line should consist of 3-foot line segments and 9-foot gaps.*